


CARING FOR YOUR ONSITE SEPTIC SYSTEM IN ALASKA

Protecting your investment...

If you own a home in Alaska, chances are that you own a septic system. A septic system is an effective method for treating household wastewater. In addition, it is cost effective and easy to maintain. Well-built systems can last 20 years or more when properly maintained. Septic system failures are a major source of groundwater pollution. Layers of soil act as a natural filter, removing microbes and other particles as water seeps through. Improperly treated water can carry bacteria and viruses that can cause gastroenteritis, fever, common cold, respiratory infections and hepatitis. Septic system maintenance is like automobile maintenance, a little effort on a regular basis can save you a lot of money and significantly prolong the life of the system.



Use Water Wisely

The more wastewater you produce, the more your tank and drainfield must treat. Continuous saturation can affect the quality of the soil and its ability to naturally remove toxins, bacteria, and viruses from the water. Use water-saving devices, repair leaky fixtures, reduce toilet reservoir volume, take shorter showers and shallower baths, and wash only full loads of dishes and laundry.

DO'S AND DON'TS

- ◆ **Don't** treat an on-site wastewater treatment system as if it were a normal centralized sewer system (Items flushed down the toilet Don't disappear).
 - Don't flush household wastes such as:**


Coffee grinds	Kitty Litter
Feminine hygiene products	Cigarette butts
Disposable diapers	Fat, grease or oil
Paper towels	
 - Don't flush hazardous chemicals, such as:**

Paints	Paint thinners
Pesticides	Varnishes
Medications	Waste oils
- ◆ **Don't** build driveways, storage buildings or other structures over the septic tank or drainfield.
- ◆ **Do** divert rainwater coming from driveways and roofs from drainfields. Flooding of the drainfield with excessive water will keep the soil from naturally cleaning the wastewater, leading to groundwater pollution.
- ◆ **Do** fix leaking faucets and toilets and install low-flow devices to help reduce the wastewater volume the system must treat.
- ◆ **Do** maintain a grass cover over drainfield area.
- ◆ **Do** use household cleaning materials in moderation. They seldom affect the operation of a septic system when used in **moderation**.
- ◆ **Do** leave stand pipes extending at least 24" above the surface. If you must cut them down be sure to measure and mark their location on a drawing of your system so they may be located for pumping maintenance in the future.

PUMP REGULARLY

Don't wait until you have a problem!

If the buildup of solids, sludge, in the tank becomes too high, solids move to the drainfield and can clog and strain the system to the point where a new drainfield will be needed. DEC recommends pumping every 2 years. If you have a garbage disposal, hot tub, or whirlpool you should increase the pumping frequency to once a year.



Scum layer is made of floating oils and greases.
Sludge layer is made of heavier solids.

Should I add chemical or biological additives to my septic tank?

Because of the cold soil temperatures typically found in Alaska, adding performance enhancing additives like yeast, bacteria or chemicals to your septic tank is of little value. In fact, in some cases, these additives can be harmful to your system or the environment. Because of this, DEC recommends **NOT** using additives and instead have your septic tank pumped every 2 years.



For more information please contact your local ADEC office

Soldotna 262-5210
Fairbanks 451-2109
Anchorage 269-7519
Juneau 465-5167
Mat-Su 376-1871